

# ConTeXt

commands

EN



# ConTeXt

## commands

en / english  
January 25, 2012



`\about {1.} [2.]`

- 1 CONTENT
- 2 REFERENCE

`\adaptlayout [...1;...] [...2.,...]`  
OPTIONAL

- 1 NUMBER
- 2 `height` = DIMENSION max
- `lines` = NUMBER

`\appendix [...1;...] {2.}`  
OPTIONAL

- 1 REFERENCE
- 2 CONTENT

`\at {1.} {2.} [3.]`

- 1 CONTENT
- 2 CONTENT
- 3 REFERENCE

`\atpage [...]`

- \* REFERENCE

`\background {*.}`

- \* CONTENT

`\blackrule [...*.,...]`  
OPTIONAL

- \* *inherits from* `\setupblackrules`

`\blackrules [...*.,...]`

- \* *inherits from* `\setupblackrules`

`\blank [...*;...]`  
OPTIONAL

- \* small medium **big** nowhite back white disable force reset line halfline FORMULA fixed flexible none always outer joinedup

`\bookmark [1.] {2.}`  
OPTIONAL

- 1 IDENTIFIER
- 2 CONTENT

`\but [...]`

- \* REFERENCE

`\button [...1.,...] {2.} [...3.,...]`  
OPTIONAL

- 1 *inherits from* `\setupbuttons`
- 2 CONTENT
- 3 REFERENCE

`\bypassblocks [...1;...] [...2.,...]`  
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\CAP {*.}`

- \* CONTENT

`\Cap {...}`

\* CONTENT

`\Caps {... ..*.. ..}`

\* WORD

`\Character {...}`

\* CONTENT

`\Characters {...}`

\* CONTENT

`\cap {...}`

\* CONTENT

`\chapter [...1...;...2.]`

1 REFERENCE  
2 CONTENT

OPTIONAL

`\character {...}`

\* CONTENT

`\characters {...}`

\* CONTENT

`\chem {...1.} {...2.} {...3.}`

1 CONTENT  
2 CONTENT  
3 CONTENT

`\clip [...1.,...2.] {...3.}`

1 *inherits from* \setupclipping  
2 CONTENT

OPTIONAL

`\clonefield [...1.] [...2.;...3.] [...4.;...]`

1 IDENTIFIER  
2 IDENTIFIER  
3 IDENTIFIER  
4 IDENTIFIER

OPTIONAL

`\color [...1.] {...2.}`

1 TEXT  
2 CONTENT

`\column`

`\comment [...1.] [...2.,...3.] {...4.}`

1 IDENTIFIER  
2 *inherits from* \setupcomment  
3 CONTENT

OPTIONAL

OPTIONAL

`\comparecolorgroup [...1.]`

\* IDENTIFIER

`\comparepalet [..]`

\* IDENTIFIER

`\completeCOMBINEDLIST [..] [.., OPTIONAL 2, ..]`

1 IDENTIFIER  
2 inherits from \setupcombinedlist

`\completelistofFLOATS`

`\completelistofSORTS`

`\completelistofSYNONYMS`

`\completeREGISTER [.., OPTIONAL *, ..]`

\* inherits from \setupregister

`\convertnumber {..} {2..}`

1 CONTENT  
2 CONTENT

`\copyfield [..] [.., 2, ..]`

1 IDENTIFIER  
2 IDENTIFIER

`\correctwhitespace {*..}`

\* CONTENT

`\coupledocument [..] [2] [3]`

1 IDENTIFIER  
2 file  
3 IDENTIFIER

`\coupledREGISTER [..] {2..}`

1 TEXT  
2 INDEX

`\couplemarking [..] [2..]`

1 IDENTIFIER  
2 IDENTIFIER

`\couplepage [..., 1, ...] [..., 2, ...]`

1 IDENTIFIER  
2 option = doublesided  
before = COMMAND  
after = COMMAND

`\couplepaper [*..]`

\* IDENTIFIER

`\coupleregister [*..]`

\* IDENTIFIER

`\crlf`

`\currentdate [...*...]`

\* *inherits from* \date

`\currentheadnumber`

`\date [...,1...][...2...]`  
                  OPTIONAL                  OPTIONAL

1 d = NUMBER

m = NUMBER

y = NUMBER

2 day month year weekday d m y w dd mm yy space -- day+ d+ dd+ referral TEXT

`\decouplemarking [...*...]`

\* IDENTIFIER

`\define [...1...] [...2...]{...3...}`  
                  OPTIONAL

1 NUMBER

2 CSNAME

3 CONTENT

`\defineblank [...1...][...2...]`

1 IDENTIFIER

2 *inherits from* \setupblank

`\defineblock [...*...]`

\* IDENTIFIER

`\definebodyfont [...1...][...2...][...3...]`  
  OPTIONAL

1 5pt ... 12pt small big

2 **rm** ss tt hw cg mm

3 tf = FILE

bf = FILE

sl = FILE

it = FILE

bs = FILE

bi = FILE

sc = FILE

mr = FILE

ex = FILE

mi = FILE

sy = FILE

ma = FILE

mb = FILE

mc = FILE

md = FILE

`\definebodyfont [...1...][...2...][...3...]`

1 IDENTIFIER

2 *inherits from* \setupbodyfont

3 *inherits from* \setupbodyfont

```

\definebodyfontenvironment [1.] [2.] [OPTIONAL,,3.,...]
1 IDENTIFIER
2 5pt ... 12pt default
3 text = DIMENSION
  script = DIMENSION
  scriptscript = DIMENSION
  x = DIMENSION
  xx = DIMENSION
  a = DIMENSION
  b = DIMENSION
  c = DIMENSION
  d = DIMENSION
  small = DIMENSION
  big = DIMENSION
  interlinespace = DIMENSION
  em = normal bold slanted boldslanted type cap small... COMMAND

```

```

\definebodyfont [1.] [2.] [3.]
1 inherits from \setupbodyfont
2 inherits from \setupbodyfont
3 IDENTIFIER

```

```

\definebuffer [*.]
* IDENTIFIER

```

```

\definecolor [1.] [OPTIONAL,,2.,...]
1 IDENTIFIER
2 r = TEXT
  g = TEXT
  b = TEXT
  c = TEXT
  m = TEXT
  y = TEXT
  k = TEXT
  s = TEXT
  h = TEXT
  t = TEXT
  a = TEXT
  p = TEXT
  e = TEXT

```

```

\definecolorgroup [1.] [OPTIONAL.] [2.] [x:y:3z=,...]
1 IDENTIFIER
2 rgb cmyk gray s
3 TRIPLET

```

```

\definecombinedlist [1.] [OPTIONAL,,2.,...] [OPTIONAL,,3.,...]
1 IDENTIFIER
2 LIST
3 inherits from \setupcombinedlist

```

```

\defineconversion [1.] [2.]
1 IDENTIFIER
2 COMMAND TEXT

```

```

\definedescription [1.] [OPTIONAL,,2.,...]
1 IDENTIFIER
2 inherits from \setupdescriptions

```

```

\definedfont [*.]
* inherits from \definefont

```

```
\defineenumeration [...1;...] [...2.] [...,3.,...]
                                OPTIONAL      OPTIONAL
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setupenumerations
```

```
\definefield [...1.] [...2.] [...3.] [...,4;...] [...5.]
                                                OPTIONAL
1 IDENTIFIER
2 text line push check radio combo choice popup
3 IDENTIFIER
4 IDENTIFIER
5 IDENTIFIER
```

```
\definefieldstack [...1.] [...,2;...] [...,3.,...]
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setupfields
```

```
\definefiguresymbol [...1.] [...2.] [...,3.,...]
                                                OPTIONAL
1 IDENTIFIER
2 TEXT
3 inherits from \setupexternalfigures
```

```
\definefloat [...1.] [...2.]
1 SINGULAR NAME
2 PLURAL NAME
```

```
\definefont [...1.] [...2.] [...3.]
                                                OPTIONAL
1 IDENTIFIER
2 FILE
3 TEXT
```

```
\definefontfeature [...1.] [...2.] [...3.]
                                                OPTIONAL
1 TEXT
2 IDENTIFIER
3 compose = no yes
  mode    = node base
  tlig    = no yes
  trep    = no yes
  script  = IDENTIFIER
  language = IDENTIFIER
  ..tag.. = no yes
```

```
\definefonthandling [...1.] [...2.] [...3.]
1 IDENTIFIER
2 IDENTIFIER
3 type = hanging hz spacing tag
  right = NUMBER
  left = NUMBER
  factor = NUMBER
  min = NUMBER
  max = NUMBER
  step = NUMBER
```

```
\definefontsynonym [...1.] [...2.] [...3.]
                                                OPTIONAL
1 TEXT
2 IDENTIFIER
3 fallbacks = IDENTIFIER
  features = IDENTIFIER
  goodies = IDENTIFIER
```

`\defineframed [.1.] [.,.2.,.]`

OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupframedtexts

`\defineframedtext [.1.] [.,.2.,.]`

OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupframedtexts

`\definehead [.1.] [.2.]`

- 1 IDENTIFIER
- 2 SECTION

`\defineindentedtext [.1.] [.,.2.,.]`

- 1 IDENTIFIER
- 2 *inherits from* \setupindentedtext

`\defineinteractionmenu [...,1...] [.,.2.,.]`

OPTIONAL

- 1 left right top bottom IDENTIFIER
- 2 *inherits from* \setupinteractionmenu

`\defineinteractionmenu [.1.] [.2.] [.,.3.,.]`

OPTIONAL

OPTIONAL

- 1 left right top bottom IDENTIFIER
- 2 left right top bottom IDENTIFIER
- 3 *inherits from* \setupinteractionmenu

`\definelabel [.1.] [.,.2.,.]`

- 1 IDENTIFIER
- 2 text = TEXT
- location = inmargin intext
- way = bytext bycd:section
- blockway = yes no
- headstyle = normal bold slanted boldslanted type cap small... COMMAND
- headcolor = IDENTIFIER
- before = COMMAND
- after = COMMAND

`\definelist [.1.] [.2.] [.,.3.,.]`

OPTIONAL

OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 *inherits from* \setuplist

`\definelogo [.1.] [.2.] [.3.] [.,.4.,.]`

- 1 IDENTIFIER
- 2 top header footer bottom
- 3 none page leftedge leftmargin left middle right rightmargin rightedge
- 4 command = COMMAND TEXT
- state = start stop

`\definemakeup [.1.] [.,.2.,.]`

- 1 IDENTIFIER
- 2 *inherits from* \setupmakeup

`\definemarking [.1.] [.2.]`

OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\defineoutput [.1.] [...,2,...]`

1 IDENTIFIER  
2 IDENTIFIER

`\defineoverlay [...,1,...] [...,2,...]`

1 IDENTIFIER  
2 COMMAND

`\definepalet [.1.] [...,2,...]`

1 IDENTIFIER  
2 IDENTIFIER = IDENTIFIER

`\definepapersize [.1.] [...,2,...]`

1 IDENTIFIER  
2 width = DIMENSION  
height = DIMENSION  
offset = DIMENSION  
scale = NUMBER

`\defineparagraphs [.1.] [...,2,...]`

1 IDENTIFIER  
2 n = NUMBER  
rule = on off  
height = fit DIMENSION  
before = COMMAND  
after = COMMAND  
inner = COMMAND  
distance = DIMENSION  
tolerance = verystrict strict tolerant verytolerant stretch  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r

`\defineprofile [...,1,...] [...,2,...]`

1 IDENTIFIER  
2 IDENTIFIER

`\defineprogram [.1.] [...,2.] [...,3.]`

1 IDENTIFIER  
2 TEXT  
3 TEXT

`\definereference [.1.] [...,2,...]`

1 IDENTIFIER  
2 REFERENCE

`\definereferenceformat [.1.] [...,2,...]`

1 IDENTIFIER  
2 left = TEXT  
right = TEXT  
text = TEXT  
label = IDENTIFIER

`\definereferencelist [.1.] [...,2,...]`

1 IDENTIFIER  
2 *inherits from* \setupreferencelist

`\defineregister [.1.] [...,2.]`

1 SINGULAR NAME  
2 PLURAL NAME

`\definesection [..]`

\* IDENTIFIER

`\definesectionblock [..] [...,2,...]`

OPTIONAL

1 *inherits from* \setupsectionblock  
2 *inherits from* \setupsectionblock

`\definesorting [..] [..] [..]`

OPTIONAL

1 SINGULAR NAME  
2 PLURAL NAME  
3 COMMAND

`\definestartstop [..] [...,2,...]`

1 IDENTIFIER  
2 before = COMMAND  
after = COMMAND  
style = normal bold slanted boldslanted type cap small... COMMAND  
commands = COMMAND

`\definesubfield [..] [..] [...3,...]`

1 IDENTIFIER  
2 IDENTIFIER  
3 IDENTIFIER

`\definesymbol [..] [..]`

1 IDENTIFIER  
2 TEXT

`\definesynonyms [..] [..] [..] [..]`

OPTIONAL

1 SINGULAR NAME  
2 PLURAL NAME  
3 COMMAND  
4 COMMAND

`\definetabletemplate [..] [..] [..] [..]`

OPTIONAL OPTIONAL

1 IDENTIFIER  
2 TEXT  
3 TEXT  
4 TEXT

`\definetabulate [..] [..] [..]`

OPTIONAL

1 IDENTIFIER  
2 IDENTIFIER  
3 TEXT

`\definetext [..] [..] [..] [..] [..]`

OPTIONAL OPTIONAL

1 IDENTIFIER  
2 header footer  
3 TEXT  
4 TEXT  
5 TEXT

`\definetype [..] [...,2,...]`

1 IDENTIFIER  
2 *inherits from* \setuptype



`\fillinline [..,1,..] .2.`

OPTIONAL

- 1 *inherits from* \setupfillinlines
- 2 NOTHING

`\fillinrules [..,1,..] {.2.} {.3.}`

OPTIONAL

OPTIONAL

- 1 *inherits from* \setupfillinrules
- 2 CONTENT
- 3 CONTENT

`\fillintext [..,1,..] {.2.} {.3.}`

OPTIONAL

OPTIONAL

- 1 *inherits from* \setupfillinrules
- 2 CONTENT
- 3 CONTENT

`\fitfield [.*]`

- \* IDENTIFIER

`\fixedspaces`

`\followprofile {.1.} [.2.]`

- 1 CONTENT
- 2 TEXT

`\followprofileversion {.1.} [.2.] [.3.]`

- 1 CONTENT
- 2 TEXT
- 3 IDENTIFIER

`\followversion {.1.} [.2.]`

- 1 CONTENT
- 2 TEXT

`\footnote [.1.] {.2.}`

OPTIONAL

- 1 REFERENCE
- 2 CONTENT

`\footnotetext [.1.] {.2.}`

OPTIONAL

- 1 REFERENCE
- 2 CONTENT

`\forceblocks [...1,...] [...2,...]`

OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\fraction {.1.} {.2.}`

- 1 CONTENT
- 2 CONTENT

`\framed [..,1,..] {.2.}`

OPTIONAL

- 1 *inherits from* \setupframed
- 2 CONTENT

`\FRAMEDTEXT [..,*,..]`

OPTIONAL

- \* *inherits from* \setupframedtexts

`\from [...]`

\* REFERENCE

`\getbuffer [...]`

\* IDENTIFIER OPTIONAL

`\getmarking [^.^.] [^.^.]`

1 IDENTIFIER  
2 first last previous both all current

`\godown [...]`

\* DIMENSION

`\goto {.^.^} {.^.^} [...^,^,...]`

1 CONTENT  
2 CONTENT  
3 REFERENCE

`\gotobox {.^.^} [...^,^,...]`

1 CONTENT  
2 REFERENCE

`\graycolor [...]`

\* TEXT

`\grid [...,^,^,...]`

\* x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
dx = NUMBER  
dy = NUMBER  
xstep = NUMBER  
ystep = NUMBER  
offset = yes no  
factor = NUMBER  
scale = NUMBER  
unit = cm pt em mm ex es in  
location = left middle

`\hairline`

`\head [...,^,...]`

\* REFERENCE OPTIONAL

`\headnumber [...]`

\* SECTION OPTIONAL

`\headtext {...}`

\* CONTENT

`\hideblocks [...^,^,...] [...^,^,...]`

1 IDENTIFIER OPTIONAL  
2 IDENTIFIER

`\high {..}`

\* CONTENT

`\hl [...]`

\* NUMBER

`\in {.1} {.2} [.3]`

1 CONTENT  
2 CONTENT  
3 REFERENCE

`\INDENTATION ...`

\* NOTHING

`\indenting [...,*...]`

\* never none not no yes always first next small medium big normal odd even DIMENSION

`\inframed [...,1,...] {.2}`  
OPTIONAL

1 inherits from \setupframed  
2 CONTENT

`\inner [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\inleft [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\inline [...]`

\* REFERENCE

`\inmargin [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\inothmargin [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\inouter [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\inright [.1] [.2] {.3}`  
OPTIONAL    OPTIONAL

1 + - low  
2 REFERENCE  
3 CONTENT

`\installlanguage [..1.] [..,2.,...]`

1 IDENTIFIER  
2 spacing = packed broad  
lefthyphenmin = NUMBER  
righthyphenmin = NUMBER  
state = start stop  
leftsentence = COMMAND  
rightsentence = COMMAND  
leftsubsentence = COMMAND  
rightsubsentence = COMMAND  
leftquote = COMMAND  
rightquote = COMMAND  
leftquotation = COMMAND  
rightquotation = COMMAND  
leftspeech = COMMAND  
middlespeech = COMMAND  
rightspeech = COMMAND  
limittext = TEXT  
date = TEXT  
compoundhyphen = COMMAND  
leftcompoundhyphen = COMMAND  
rightcompoundhyphen = COMMAND  
default = IDENTIFIER

`\interactionbar [..,*.,...]`

\* inherits from \setupinteractionbar

`\interactionbuttons [..,1.,...] [...2;...]`

1 inherits from \setupinteractionbar  
2 IDENTIFIER

`\item [..,*.,...]`

OPTIONAL  
\* REFERENCE

`\items [..,1.,...] {...2. ..}`

OPTIONAL  
1 inherits from \setupitems  
2 CONTENT

`\its [..,*.,...]`

OPTIONAL  
\* REFERENCE

`\keepblocks [..,1.,...] [...2.,...]`

OPTIONAL  
1 IDENTIFIER  
2 all IDENTIFIER

`\LABELING [..*.]`

OPTIONAL  
\* REFERENCE

`\labels [..*.]`

\* IDENTIFIER

`\labeltext {..*}`

\* CONTENT

`\language [..*.]`

\* nl fr en uk de es cz ..

`\leftaligned {...}`

\* CONTENT

`\listsymbol [..] {..}`

1 IDENTIFIER  
2 CONTENT

`\loadSORTS`

`\loadSYNONYMS`

`\logfields`

`\lohi [..] {..} {..}`

OPTIONAL  
1 low  
2 CONTENT  
3 CONTENT

`\low {...}`

\* CONTENT

`\MONTH {...}`

\* CONTENT

`\mainlanguage [..]`

\* nl fr en uk de es cz ..

`\mapfontsize [..] [..]`

1 DIMENSION  
2 DIMENSION

`\mar [...1,...] {..}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\marginrule [..] {..}`

1 NUMBER  
2 CONTENT

`\margintext [..] [..] {..}`

OPTIONAL OPTIONAL  
1 + - low  
2 REFERENCE  
3 CONTENT

`\marking [..] {..}`

1 IDENTIFIER  
2 CONTENT

`\markversion`

`\mathematics {...}`

\* CONTENT

`\mediaeval {...}`

\* CONTENT

`\midaligned {...}`

\* CONTENT

`\mirror {...}`

\* CONTENT

`\month {...}`

\* CONTENT

`\moveongrid [...*,...]`

\* OPTIONAL  
`standard` top both bottom -top -both -bottom TEXT high middle low page broad fit depth line reset none  
DIMENSION

`\name {...}`

\* CONTENT

`\nextSECTION`

`\nocap {...}`

\* CONTENT

`\noheaderandfooterlines`

`\noindenting`

`\nolist {...}`

\* CONTENT

`\nomarking {...}`

\* CONTENT

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note [...]`

\* REFERENCE

`\notopandbottomlines`

`\nowhitespace`

`\numbers {...}`

\* CONTENT

`\overbar {...}`

\* CONTENT

`\overbars {...}`

\* WORD

`\overstrike {...}`

\* CONTENT

`\overstrikes {...}`

\* WORD

`\packed`

`\page [...;...]`

\* `yes` `makeup` `no` `preference` `bigpreference` `left` `right` `disable` `last` `quadruple` `even` `odd` `blank` `empty` `reset` `start` `stop`

`\pagereference [...]`

\* REFERENCE

`\PARAGRAPH`

`\part [...1;...] {...2}`

OPTIONAL

1 REFERENCE

2 CONTENT

`\periods [...]`

\* NUMBER

`\placebookmarks [...1;...] [...2;...] [...3,...]`

OPTIONAL

OPTIONAL

OPTIONAL

1 IDENTIFIER

2 IDENTIFIER all

3 force = yes no

`\placecombinedlist [...1.] [...2,...]`

OPTIONAL

1 IDENTIFIER

2 *inherits from* `\setupcombinedlist`

`\placeCOMBINEDLIST [...1.] [...2,...]`

OPTIONAL

1 IDENTIFIER

2 *inherits from* `\setupcombinedlist`

`\placeFLOAT [...1.] [...2;...] {...3} {...4}`

OPTIONAL

OPTIONAL

1 `left` `right` `here` `top` `bottom` `inleft` `inright` `inmargin` `margin` `leftmargin` `rightmargin` `leftedge` `rightedge`  
`innermargin` `outermargin` `inneredge` `outeredge` `inner` `outer` `line` `high` `low` `fit` `page` `leftpage` `rightpage` `opposite`  
`always` `auto` `force` `tall` `reset` `line` `height` `depth` `split` 90 180 270

2 REFERENCE

3 CONTENT

4 CONTENT

`\placefootnotes [...,*,...]`

OPTIONAL

\* *inherits from* `\setupfootnotes`

`\placeformula [...1,...] {2.} $$$3$$$`

OPTIONAL      OPTIONAL

- 1 REFERENCE
- 2 CONTENT
- 3 DISPLAY MATH

`\placelegend {1.} {2.}`

- 1 CONTENT
- 2 CONTENT

`\placelist [...1,...] [...,2,...]`

OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* `\setuplist`

`\placelistofFLOATS`

`\placelistofSORTS`

`\placelistofSYNONYMS`

`\placelocalfootnotes [...,*,...]`

OPTIONAL

\* *inherits from* `\setupfootnotes`

`\placelogos [...,*,...]`

OPTIONAL

\* IDENTIFIER

`\placeongrid [1.] {2.}`

OPTIONAL

- 1 *inherits from* `\moveongrid`
- 2 CONTENT

`\placeontopofeachother {1.} {2.}`

- 1 CONTENT
- 2 CONTENT

`\placereferencelist [...,*,...]`

\* IDENTIFIER

`\placeregister [1.] [...,2,...]`

OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* `\setupregister`

`\placeREGISTER [...,*,...]`

OPTIONAL

\* *inherits from* `\setupregister`

`\placesidebyside {1.} {2.}`

- 1 CONTENT
- 2 CONTENT

`\placesubformula [...1,...] {..2.} $$..3.$$`

1 REFERENCE  
2 CONTENT  
3 DISPLAY MATH

`\position (...1,...) {..2.}`

1 POSITION  
2 CONTENT

`\processblocks [...1,...] [...2,...]`

1 IDENTIFIER  
2 IDENTIFIER

`\processpage [...1,...] [..2.]`

1 IDENTIFIER  
2 `yes no`

`\program [..*.]`

\* IDENTIFIER

`\publication [..*.]`

\* REFERENCE

`\quotation {..*..}`

\* CONTENT

`\quote {..*..}`

\* CONTENT

`\Romannumerals {..*..}`

\* CONTENT

`\ran {..*..}`

\* CONTENT

`\ref [..1.] [..2.]`

1 `t p r s e`  
2 REFERENCE

`\reference [..1.] {..2.}`

1 REFERENCE  
2 CONTENT

`\referral [...,*.,...]`

\* `bet = TEXT`  
   `ken = TEXT`  
   `dat = TEXT`  
   `van = TEXT`  
   `aan = TEXT`  
   `ref = TEXT`

`\referraldate`

`\REGISTER` [<sup>1</sup>.] {..<sup>2</sup>..+..}

OPTIONAL

- 1 TEXT
- 2 INDEX

`\reserveFLOAT` [..<sub>1</sub>..<sup>1</sup>..<sup>2</sup>..<sup>3</sup>..<sup>4</sup>..] [<sup>2</sup>.] [<sup>3</sup>..<sup>3</sup>..<sup>4</sup>..] {..<sup>4</sup>..}

OPTIONAL

OPTIONAL

OPTIONAL

- 1 height = DIMENSION  
width = DIMENSION  
frame = on off
- 2 TEXT
- 3 REFERENCE
- 4 CONTENT

`\reset` [..,\*..]

- \* IDENTIFIER

`\resetmarking` [.\*..]

- \* IDENTIFIER

`\resettextcontent` [<sup>1</sup>.] [<sup>2</sup>.] [<sup>3</sup>..<sup>3</sup>..]

OPTIONAL

- 1 top header text footer bottom
- 2 text margin edge
- 3 lefttext middletext righttext

`\rightaligned` {.\*..}

- \* CONTENT

`\romannumerals` {.\*..}

- \* CONTENT

`\rotate` [..<sub>1</sub>..<sup>1</sup>..<sup>2</sup>..] {..<sup>2</sup>..}

OPTIONAL

- 1 inherits from `\setuprotate`
- 2 CONTENT

`\scale` [..<sub>1</sub>..<sup>1</sup>..<sup>2</sup>..] {..<sup>2</sup>..}

OPTIONAL

- 1 sx = NUMBER  
sy = NUMBER
- 2 CONTENT

`\screen`

`\section` [..<sup>1</sup>..<sup>2</sup>..] {..<sup>2</sup>..}

OPTIONAL

- 1 REFERENCE
- 2 CONTENT

`\seeREGISTER` [<sup>1</sup>.] {..<sup>2</sup>..} {..<sup>3</sup>..+..}

OPTIONAL

- 1 TEXT
- 2 CONTENT
- 3 INDEX

`\selectblocks` [..<sup>1</sup>..<sup>2</sup>..<sup>3</sup>..<sup>3</sup>..] [<sup>2</sup>..<sup>2</sup>..<sup>3</sup>..<sup>3</sup>..] [<sub>1</sub>..<sub>1</sub>..<sub>2</sub>..<sub>2</sub>..]

OPTIONAL

OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 criterium = all SECTION

`\selectpaper [...,*,...]`

\* family = 1 2

`\selectversion`

`\settextcontent [.1.] [.2.] [.3.] [.4.] [.5.]`  
OPTIONAL OPTIONAL OPTIONAL

1 top header text footer bottom  
2 text margin edge  
3 TEXT SECTION date MARK pagenumber  
4 TEXT SECTION date MARK pagenumber  
5 TEXT SECTION date MARK pagenumber

`\setupalign [...,*,...]`

\* width left right middle inner outer wide broad height bottom line reset hanging nothanging hyphenated  
nothyphenated lesshyphenation morehyphenation new old normal yes no flushleft flushright flushouter flushinner  
center hz nohz spacing nospacing tolerant verytolerant stretch lefttoright righttoleft

`\setuparranging [...,*,...]`

\* disable 2\*16 2\*8 2\*4 2\*2 2\*\*2 2\*2\*4 2\*4\*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided negative  
background 90 180 270

`\setupbackground [...,*,...]`

\* leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
before = COMMAND  
after = COMMAND  
state = start stop  
inherits from \setupframed

`\setupbackgrounds [.1.] [...,2,...] [...,3,...]`  
OPTIONAL OPTIONAL

1 top header TEXT footer bottom page paper leftpage rightpage  
2 leftedge leftmargin TEXT rightmargin rightedge  
3 state = start stop cd:repeat  
inherits from \setupframed

`\setupblackrules [...,*,...]`

\* width = DIMENSION max  
height = DIMENSION max  
depth = DIMENSION max  
alternative = a b  
distance = DIMENSION  
n = NUMBER  
color = IDENTIFIER

`\setupblank [...,*]`

OPTIONAL  
\* normal default standard line halfline DIMENSION big medium small fixed flexible global unknown

`\setupblock [...,1,...] [...,2,...]`

1 IDENTIFIER  
2 before = COMMAND  
after = COMMAND  
inner = COMMAND  
style = normal bold slanted boldslanted type cap small... COMMAND  
file = FILE

`\setupbodyfont [...,*,...]`

\* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt



### \setupclipping [..,.\*,..]

\* state = start stop  
n = NUMBER  
nx = NUMBER  
ny = NUMBER  
x = NUMBER  
y = NUMBER  
sx = NUMBER  
sy = NUMBER  
width = DIMENSION  
height = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
offset = DIMENSION  
leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
mp = IDENTIFIER

### \setupcolor [..\*]

\* IDENTIFIER

### \setupcolors [..,.\*,..]

\* state = start stop global local  
conversion = yes no always never  
reduction = yes no  
rgb = yes no  
cmyk = yes no  
mpcmyk = yes no  
mpspot = yes no  
factor = yes no  
textcolor = IDENTIFIER  
split = c m y k p s no IDENTIFIER  
criterium = all none  
intent = none overprint knockout

### \setupcolumns [..,.\*,..]

\* n = NUMBER  
ntop = NUMBER  
rule = on off  
height = DIMENSION  
tolerance = OPTIONAL verystrict strict tolerant verytolerant stretch  
distance = DIMENSION  
balance = yes no  
align = text inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
blank = fixed halflines line flexible big medium small  
option = background  
direction = left right  
*inherits from \setupframed*

### \setupcombinations [..,.\*,..]

\* before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
distance = DIMENSION  
height = DIMENSION fit  
width = DIMENSION fit  
location = top middle bottom left right  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER

### \setupcombinedlist [<sup>1</sup>..] [<sub>2</sub>..,.\*,..]

1 IDENTIFIER  
2 level = 1 2 3 4 SECTION current  
*inherits from \setuplist*

`\setupcomment [..,*..]`

\* state = start stop  
width = DIMENSION  
height = DIMENSION  
color = IDENTIFIER  
title = TEXT  
space = yes no  
symbol = normal New Balloon Addition Help Paragraph Key IDENTIFIER  
option = max buffer  
margin = DIMENSION  
distance = DIMENSION

`\setupdescriptions [...1...] [...2..]`

OPTIONAL

1 IDENTIFIER  
2 style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
width = fit broad DIMENSION  
distance = DIMENSION  
sample = TEXT  
text = TEXT  
closesymbol = TEXT  
closecommand = \...#1  
closesymbol = TEXT  
titleleft = TEXT  
titleright = TEXT  
titledistance = DIMENSION  
titlestyle = normal bold slanted boldslanted type cap small... COMMAND  
titlecolor = IDENTIFIER  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
margin = standard yes no DIMENSION  
location = left right top serried inmargin inleft inright hanging  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
headcolor = IDENTIFIER  
headcommand = COMMAND  
hang = fit broad NUMBER  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
indentnext = yes no  
indenting = never none not no yes always first next small medium big normal odd even DIMENSION  
command = COMMAND  
display = yes no

`\setupenumerations [...1...] [...2..]`

OPTIONAL

1 IDENTIFIER  
2 *inherits from* \setupdescriptions

`\setupexternalfigures [.*.]`

```
* scale = NUMBER
yscale = NUMBER
yscale = NUMBER
factor = max fit broad
wfactor = NUMBER max broad fit
hfactor = NUMBER max broad fit
width = DIMENSION
height = DIMENSION
frame = on off
preset = yes no
display = FILE
preview = yes no
repeat = yes no
object = yes no
type = eps mps pdf tif png jpg mov cd:tex
method = eps mps pdf tif png jpg mov cd:tex
option = frame empty test
frames = on off
ymax = NUMBER
xmax = NUMBER
directory = TEXT
location = local global default none
maxwidth = DIMENSION
maxheight = DIMENSION
conversion = TEXT
prefix = TEXT
interaction = yes no
```

`\setupfield [..1.] [..2,...] [..3,...1] [..4,...1] [..5,...1]`

```
1 IDENTIFIER
2 label horizontal vertical frame
3 inherits from \setupfields
4
5
```

`\setupfields [...1,...] [...2,...1] [...3,...1] [...4,...1]`

```
1 reset label horizontal vertical frame
2 n = NUMBER
distance = DIMENSION
before = COMMAND
after = COMMAND
inbetween = COMMAND
color = IDENTIFIER
style = normal bold slanted boldslanted type cap small... COMMAND
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l
12r
option = readonly required protected sorted unavailable hidden printable
clickin = REFERENCE
clickout = REFERENCE
regionin = REFERENCE
regionout = REFERENCE
afterkey = REFERENCE
format = REFERENCE
validate = REFERENCE
calculate = REFERENCE
fieldoffset = DIMENSION
fieldframecolor = IDENTIFIER
fieldbackgroundcolor = IDENTIFIER
inherits from \setupframed
3 inherits from \setupfields
4 inherits from \setupfields
```

`\setupfillinlines [..*,...]`

```
* width = DIMENSION
margin = DIMENSION
distance = DIMENSION
before = COMMAND
after = COMMAND
```

`\setupfillinrules [..,*.,..]`

\* width = fit broad DIMENSION  
distance = DIMENSION  
before = COMMAND  
after = COMMAND  
style = normal bold slanted boldslanted type cap small... COMMAND  
n = NUMBER  
interlinespace = small medium big  
separator = TEXT

`\setupfloat [.1.] [..,2.,..]`

1 IDENTIFIER  
2 height = DIMENSION  
width = DIMENSION  
maxheight = DIMENSION  
maxwidth = DIMENSION  
minwidth = DIMENSION  
default = IDENTIFIER  
pageboundaries = LIST  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
location = left middle right  
*inherits from \setupframed*

`\setupfloats [..,*.,..]`

\* location = left right middle  
width = fit DIMENSION  
before = COMMAND  
after = COMMAND  
margin = DIMENSION  
spacebefore = small medium big none  
spaceafter = small medium big none  
sidespacebefore = small medium big none  
sidespaceafter = small medium big none  
indentnext = yes no  
ntop = NUMBER  
nbottom = NUMBER  
nlines = NUMBER  
default = IDENTIFIER  
tolerance = 0 1 2  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
sidealign = normal line  
numbering = yes nocheck  
*inherits from \setupframed*

`\setupfloatsplitting [..,*.,..]`

\* conversion = numbers characters Characters romannumerals Romannumerals  
lines = NUMBER

`\setupfonthandling [.1.] [.2.]`

1 IDENTIFIER  
2 *inherits from \definefonthandling*

`\setupfontsynonym [.1.] [.2.]`

1 IDENTIFIER  
2 *inherits from \definefontsynonym*

`\setupfooter [.1.] [..,2.,..]`

OPTIONAL  
1 *inherits from \setupheader*  
2 *inherits from \setupheader*

`\setupfootertexts [.1.] [.2.] [.3.]`

OPTIONAL  
1 text margin edge  
2 TEXT SECTION date MARK pagenumber  
3 TEXT SECTION date MARK pagenumber

`\setupfootnotedefinition [..,*.,..]`

\* inherits from `\setupdescriptions`

`\setupfootnotes [..,*.,..]`

\* conversion = numbers characters Characters romannumerals Romannumerals  
way = bytext bycd:section  
location = page TEXT columns firstcolumn lastcolumn high none  
rule = on off  
before = COMMAND  
after = COMMAND  
width = DIMENSION  
height = DIMENSION  
bodyfont = 5pt ... 12pt small big  
style = normal bold slanted boldslanted type cap small... COMMAND  
distance = DIMENSION  
columndistance = DIMENSION  
margindistance = DIMENSION  
n = NUMBER  
numbercommand = `\...#1`  
textcommand = `\...#1`  
split = tolerant strict verystRICT NUMBER  
textstyle = normal bold slanted boldslanted type cap small... COMMAND  
textcolor = IDENTIFIER  
interaction = yes no  
paragraph = yes no  
factor = NUMBER  
inherits from `\setupframed`

`\setupforms [..,*.,..]`

\* method = HTML FDF

`\setupformulas [..,*.,..]`

\* location = left right  
left = TEXT  
right = TEXT  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
option = middle  
strut = yes no  
distance = DIMENSION  
margin = DIMENSION standard yes no  
align = flushleft flushright middle center  
leftmargin = DIMENSION  
rightmargin = DIMENSION  
indentnext = yes no  
alternative = IDENTIFIER  
spacebefore = DIMENSION  
after = DIMENSION  
separator = TEXT  
conversion = numbers characters Characters romannumerals Romannumerals TEXT

`\setupframed` [<sup>1</sup>...] [<sub>OPTIONAL</sub>,<sup>2</sup>\_,...]

1 IDENTIFIER  
2 height = fit broad DIMENSION  
width = fit broad fixed local DIMENSION  
autowidth = yes no force  
offset = none overlay default DIMENSION  
location = depth hanging high lohi low top middle bottom keep  
option = none empty  
strut = yes no global local  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l  
l2r  
bottom = COMMAND  
top = COMMAND  
frame = on off none overlay  
topframe = on off  
bottomframe = on off  
leftframe = on off  
rightframe = on off  
frameoffset = DIMENSION  
framedepth = DIMENSION  
framecorner = round rectangular  
frameradius = DIMENSION  
framecolor = IDENTIFIER  
background = screen color none foreground IDENTIFIER  
backgroundscreen = NUMBER  
backgroundcolor = IDENTIFIER  
backgroundoffset = frame DIMENSION  
backgrounddepth = DIMENSION  
backgroundcorner = round rectangular  
backgroundradius = DIMENSION  
depth = DIMENSION  
corner = round rectangular  
radius = DIMENSION  
empty = yes no  
foregroundcolor = IDENTIFIER  
foregroundstyle = normal bold slanted boldslanted type cap small... COMMAND  
rulethickness = DIMENSION

`\setupframedtexts` [<sup>1</sup>...] [<sub>OPTIONAL</sub>,<sup>2</sup>\_,...]

1 IDENTIFIER  
2 bodyfont = 5pt ... 12pt small big  
style = normal bold slanted boldslanted type cap small... COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND  
inner = COMMAND  
linecorrection = on off  
depthcorrection = on off  
margin = standard yes no  
location = left right middle none  
indenting = never none not no yes always first next small medium big normal odd even DIMENSION  
*inherits from \setupframed*

`\setuphead [...1,...] [...2,...,...]`

1 SECTION  
2 style = normal bold slanted boldslanted type cap small... COMMAND  
textstyle = normal bold slanted boldslanted type cap small... COMMAND  
numberstyle = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
textcolor = IDENTIFIER  
numbercolor = IDENTIFIER  
number = yes no  
ownnumber = yes no  
page = left right yes  
continue = yes no  
header = none empty high nomarking  
text = none empty high nomarking  
footer = none empty high nomarking  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
alternative = normal inmargin middle TEXT  
hang = none broad fit line NUMBER  
command = \...#1#2  
numbercommand = \...#1  
textcommand = \...#1  
deepnumbercommand = \...#1  
deeptextcommand = \...#1  
prefix = + - TEXT  
placehead = yes no empty  
incrementnumber = yes no LIST FILE  
resetnumber = yes no  
file = IDENTIFIER  
expansion = yes no command  
margintext = yes no  
interaction = list none  
*inherits from \setupheads*

`\setupheader [...1,...] [...2,...,...]`

OPTIONAL  
1 TEXT margin edge  
2 state = normal stop start empty high none nomarking IDENTIFIER  
strut = yes no  
style = normal bold slanted boldslanted type cap small... COMMAND  
leftstyle = normal bold slanted boldslanted type cap small... COMMAND  
rightstyle = normal bold slanted boldslanted type cap small... COMMAND  
leftwidth = DIMENSION  
rightwidth = DIMENSION  
before = COMMAND  
after = COMMAND

`\setupheadertexts [...1,...] [...2,...] [...3,...]`

OPTIONAL  
1 text margin edge  
2 TEXT SECTION date MARK pagenumber  
3 TEXT SECTION date MARK pagenumber

`\setupheadnumber [...1,...] [...2,...]`

1 SECTION  
2 NUMBER +cd:number -cd:number

`\setupheads [...,*...,...]`

\* sectionnumber = yes NUMBER no  
alternative = normal margin middle TEXT paragraph  
separator = TEXT  
stopper = TEXT  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
aligntitle = yes float no  
tolerance = verystrict strict tolerant verytolerant stretch  
indentnext = yes no  
command = \...#1#2  
margin = DIMENSION

`\setupheadtext` [1.] [2.]

OPTIONAL

1 nl fr en uk de es cz ..  
2 IDENTIFIER = TEXT

`\setuphyphenmark` [\*.]

\* sign = -- --- - ~ ( ) = /

`\setupindentedtext` [...1...] [...2...]

OPTIONAL

1 IDENTIFIER  
2 style = normal bold slanted boldslanted type cap small... COMMAND  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
width = fit DIMENSION  
text = TEXT  
sample = TEXT  
before = COMMAND  
after = COMMAND  
distance = DIMENSION  
separator = TEXT

`\setupindenting` [...\*...]

\* never none not no yes always first next small medium big normal odd even DIMENSION

`\setupinmargin` [1.] [...2...]

OPTIONAL

1 left right NUMBER  
2 location = left right both  
style = normal bold slanted boldslanted type cap small... COMMAND  
before = COMMAND  
after = COMMAND  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
line = NUMBER  
distance = DIMENSION  
separator = TEXT  
width = DIMENSION  
distance = DIMENSION  
stack = yes no  
*inherits from \setupframed*

`\setupinteraction` [...\*...]

\* state = start stop  
menu = on off  
page = yes no  
click = yes no  
split = yes no  
display = new  
openaction = REFERENCE  
closeaction = REFERENCE  
openpageaction = REFERENCE  
closepageaction = REFERENCE  
calculate = IDENTIFIER  
strut = yes no  
width = DIMENSION  
height = DIMENSION  
depth = DIMENSION  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
contrastcolor = IDENTIFIER  
symbolset = IDENTIFIER  
title = TEXT  
subtitle = TEXT  
author = TEXT  
date = TEXT  
keyword = TEXT  
fieldlayer = auto IDENTIFIER

`\setupinteractionbar [..,*.,..]`

\* state = start stop  
alternative = a b c d e f g  
symbol = yes no  
width = DIMENSION height fit  
height = DIMENSION height fit  
depth = DIMENSION  
color = IDENTIFIER  
step = NUMBER small medium big  
*inherits from \setupframed*

`\setupinteractionmenu [...1,...] [...2,...]`

1 IDENTIFIER  
2 before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
left = COMMAND  
right = COMMAND  
middle = COMMAND  
state = start stop none local  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
contrastcolor = IDENTIFIER  
distance = overlay DIMENSION  
samepage = yes empty no none  
unknownreference = yes empty no none  
leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
position = yes no  
*inherits from \setupframed*

`\setupinteractionscreen [..,*.,..]`

\* width = DIMENSION fit max  
height = DIMENSION fit max  
backspace = DIMENSION  
topspace = DIMENSION  
horoffset = DIMENSION  
veroffset = DIMENSION  
option = max fit doublesided singlesided auto none bookmark  
delay = NUMBER none

`\setupinterlinespace [.*.]`

\* reset small medium auto big on off  
OPTIONAL

`\setupinterlinespace [..,*.,..]`

\* height = NUMBER  
depth = NUMBER  
line = DIMENSION  
top = NUMBER  
bottom = NUMBER

`\setupitemgroup` [1.] [2.] [3.;...] [4.;...]

OPTIONAL            OPTIONAL            OPTIONAL

1 IDENTIFIER  
2 NUMBER each  
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargin autointro loose  
repeat SECTION paragraph intext random reverse  
4 margin = no standard DIMENSION  
leftmargin = no standard DIMENSION  
rightmargin = no standard DIMENSION  
width = DIMENSION  
distance = DIMENSION  
step = DIMENSION  
factor = NUMBER  
items = NUMBER  
start = NUMBER  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
left = TEXT  
right = TEXT  
beforehead = COMMAND  
afterhead = COMMAND  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
marstyle = normal bold slanted boldslanted type cap small... COMMAND  
symstyle = normal bold slanted boldslanted type cap small... COMMAND  
stopper = TEXT  
n = NUMBER  
symbol = NUMBER  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
symalign = left right flushleft flushright middle center  
indentnext = yes no  
textdistance = none big medium small

`\setupitems` [...,\*...]

\* location = left right inmargin top bottom  
symbol = 1 2 ... n a ... TEXT none  
width = DIMENSION  
n = NUMBER unknown  
before = COMMAND  
inbetween = COMMAND  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
after = COMMAND

`\setuplabeltext` [1.] [2.]

OPTIONAL

1 nl fr en uk de es cz ..  
2 IDENTIFIER = TEXT

`\setuplanguage` [1.] [...,2.;...]

1 nl fr en uk de es cz ..  
2 inherits from \installlanguage

## `\setuplayout [..,*.,..]`

```
* width           = DIMENSION fit middle
height           = DIMENSION fit middle
backspace        = DIMENSION
topspace         = DIMENSION
margin           = DIMENSION
leftmargin       = DIMENSION
rightmargin      = DIMENSION
header           = DIMENSION
footer          = DIMENSION
top              = DIMENSION
bottom          = DIMENSION
leftedge         = DIMENSION
rightedge        = DIMENSION
headerdistance   = DIMENSION
footerdistance   = DIMENSION
topdistance      = DIMENSION
bottomdistance   = DIMENSION
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
leftedgedistance = DIMENSION
rightedgedistance = DIMENSION
horoffset        = DIMENSION
veroffset        = DIMENSION
style            = normal bold slanted boldslanted type cap small... COMMAND
color            = IDENTIFIER
marking          = on off color screen TEXT page
location         = left middle right bottom top singlesided doublesided
scale            = DIMENSION
nx               = NUMBER
ny               = NUMBER
dx               = DIMENSION
dy               = DIMENSION
lines            = NUMBER
columns          = NUMBER
columndistance   = DIMENSION
grid             = yes no
bottomspace      = DIMENSION
cutspace         = DIMENSION
textdistance     = DIMENSION
textwidth        = NUMBER
textmargin       = DIMENSION
clipoffset       = DIMENSION
page             = IDENTIFIER
paper            = IDENTIFIER
```

## `\setuplegend [..,*.,..]`

```
* n               = NUMBER
distance          = DIMENSION
inbetween         = COMMAND
width             = DIMENSION
height           = DIMENSION
location         = right bottom
bodyfont         = 5pt ... 12pt small big
```

## `\setuplinenumbering [..,*.,..]`

```
* conversion      = numbers characters Characters romannumerals Romannumerals TEXT
start             = NUMBER
step              = NUMBER
width             = DIMENSION
location         = middle left margin inmargin inleft right inright inner outer text begin end
style             = normal bold slanted boldslanted type cap small... COMMAND
prefix           = TEXT
referencing       = on off
```

## `\setuplines [..,*.,..]`

```
* before          = COMMAND
after             = COMMAND
inbetween         = COMMAND
indenting         = never none not no yes always first next small medium big normal odd even DIMENSION
space             = yes no
option            = packed
```

`\setuplinewidth [..]`

\* DIMENSION

`\setuplist [...1,...] [...,2,...]`

```
1 IDENTIFIER
2 state = start stop
  alternative = a b c ... none command
  coupling = on off
  criterium = SECTION local previous current here intro all
  extras = LIST
  style = normal bold slanted boldslanted type cap small... COMMAND
  numberstyle = normal bold slanted boldslanted type cap small... COMMAND
  textstyle = normal bold slanted boldslanted type cap small... COMMAND
  pagestyle = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  command = \...#1#2#3
  numbercommand = \...#1
  textcommand = \...#1
  pagecommand = \...#1
  interaction = sectionnumber text pagenumber all none
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  left = TEXT
  right = TEXT
  label = yes no
  prefix = yes no none
  pagenumber = yes no
  headnumber = yes no
  cd:sectionnumber = yes no
  aligntitle = yes no
  margin = DIMENSION
  width = DIMENSION fit
  height = DIMENSION fit broad
  depth = DIMENSION fit broad
  distance = DIMENSION
  separator = TEXT
  stopper = TEXT
  symbol = none 1 2 3 ...
  expansion = yes no command
  maxwidth = DIMENSION
  order = command all normal
inherits from \setupframed
```

`\setuplistalternative [.1.] [...,2,...]`

```
1 a b c
2 command = COMMAND
  width = DIMENSION
  stretch = DIMENSION
  distance = DIMENSION
```

`\setupmakeup [.1.] [...,2,...]`

```
1 IDENTIFIER
2 width = DIMENSION
  height = DIMENSION
  page = left yes right
  commands = COMMAND
  doublesided = yes no empty
  headerstate = normal stop start empty none nomarking
  footerstate = normal stop start empty none nomarking
  textstate = normal stop start empty none nomarking
  topstate = stop start
  bottomstate = stop start
  pagestate = stop start
  color = IDENTIFIER
```

`\setupmarginblocks [.,.*.,..]`

\* location = inmargin left middle right  
style = normal bold slanted boldslanted type cap small... COMMAND  
width = DIMENSION  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
top = COMMAND  
inbetween = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND

`\setupmarginrules [.*.]`

\* level = NUMBER  
rulethickness = DIMENSION

`\setupmarking [.1.] [.2.]`

1 IDENTIFIER  
2 state = start stop  
separator = COMMAND  
expansion = yes no

`\setupnarrower [.,.*.,..]`

\* left = DIMENSION  
right = DIMENSION  
middle = DIMENSION

`\setupnumbering [.,.*.,..]`

\* way = bytext bycd:section  
state = start stop

`\setupoppositeplacing [.*.]`

\* state = start stop  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND

`\setupoutput [...*...]`

\* IDENTIFIER

`\setuppagenumber [...,*...]`

\* number = NUMBER  
state = start stop keep

`\setuppagenumbering [...,*...]`

\* alternative = singlesided doublesided  
location = header footer left right middle margin marginedge inleft inright  
conversion = numbers characters Characters romannumerals Romannumerals  
style = normal bold slanted boldslanted type cap small... COMMAND  
left = TEXT  
right = TEXT  
way = bytext bycd:section  
text = TEXT  
numberseparator = TEXT  
textseparator = TEXT  
cd:sectionnumber = yes no  
separator = TEXT  
strut = yes no  
state = start stop  
width = DIMENSION  
command = \...#1  
page = last yes no

`\setuppagetransitions [...,*,...]`

OPTIONAL

\* reset NUMBER

`\setuppalet [...]`

\* IDENTIFIER

`\setuppaper [...,*,...]`

\* paper = IDENTIFIER  
page = IDENTIFIER  
nx = NUMBER  
ny = NUMBER  
width = DIMENSION  
height = DIMENSION  
topspace = DIMENSION  
backspace = DIMENSION  
option = max fit  
method = normal IDENTIFIER

`\setuppapersize [...1,...] [...2,...]`

OPTIONAL

1 A3 A4 A5 A6 letter ... CD IDENTIFIER landscape mirrored rotated 90 180 270  
2 negative inherits from \setuppapersize

`\setupparagraphnumbering [...,*,...]`

\* state = start stop reset line  
style = normal bold slanted boldslanted type cap small... COMMAND  
distance = DIMENSION

`\setupparagraphs [...1.] [...2.] [...3.,...]`

OPTIONAL

1 IDENTIFIER  
2 NUMBER each  
3 style = normal bold slanted boldslanted type cap small... COMMAND  
width = DIMENSION  
height = DIMENSION  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l l2r  
tolerance = verystrict strict tolerant verytolerant stretch  
distance = DIMENSION  
before = COMMAND  
after = COMMAND  
inner = COMMAND  
command = COMMAND  
rule = on off

`\setuppositioning [...,*,...]`

\* state = start overlay  
unit = cm pt em mm ex es in  
factor = NUMBER  
scale = NUMBER  
offset = yes no  
xstep = absolute relative  
ystep = absolute relative

`\setupprofiles [...,*,...]`

\* option = test

`\setupprograms [...,*,...]`

\* directory = TEXT

`\setuppuplications [...,*,...]`

\* alternative = apa normal  
inherits from \setupenumerations

`\setupquote [..,*.,..]`

\* before = COMMAND  
after = COMMAND  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
location = TEXT margin

`\setupreferencelist [..1.] [..,2.,..]`

1 IDENTIFIER  
2 state = start stop  
criterium = SECTION local previous all  
command = COMMAND  
before = COMMAND  
after = COMMAND

`\setupreferencing [..,*.,..]`

\* state = start stop  
cd:sectionnumber = yes no  
prefix = + - TEXT  
interaction = label TEXT all symbol  
width = DIMENSION  
left = COMMAND  
right = COMMAND  
convertfile = yes no small big  
separator = TEXT  
autofile = yes no page  
global = yes no  
export = yes no

`\setupregister [..1.] [..2.] [..,3.,..]`

1 SINGULAR NAME  
2 IDENTIFIER  
3 n = NUMBER  
balance = yes no  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l  
style = normal bold slanted boldslanted type cap small... COMMAND  
pagestyle = normal bold slanted boldslanted type cap small... COMMAND  
textstyle = normal bold slanted boldslanted type cap small... COMMAND  
indicator = yes no  
coupling = yes no  
cd:sectionnumber = yes no  
criterium = SECTION local all  
distance = DIMENSION  
symbol = 1 2 ... n a ... none  
interaction = pagenumber TEXT  
expansion = yes no command  
referencing = on off  
command = \...#1  
location = left middle right  
maxwidth = DIMENSION  
unknownreference = empty none  
alternative = a b A B  
prefix = both first none  
compress = no yes  
deeptextcommand = \...#1

`\setuprotate [..,*.,..]`

\* rotation = NUMBER  
location = normal high fit broad depth  
*inherits from \setupframed*

`\setupscreens [..,*.,..]`

\* method = dot rule external  
resolution = NUMBER  
factor = NUMBER  
screen = NUMBER

`\setupsection` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPTIONAL</sub>...]

1 IDENTIFIER  
2 IDENTIFIER  
3 conversion = numbers characters Characters romannumerals Romannumerals  
previousnumber = yes no

`\setupsectionblock` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPTIONAL</sub>...]

1 IDENTIFIER  
2 number = yes no  
page = yes right  
before = COMMAND  
after = COMMAND

`\setupsorting` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPTIONAL</sub>...]

1 IDENTIFIER  
2 before = COMMAND  
after = COMMAND  
command = \...#1  
state = start stop  
criterium = all used  
style = normal bold slanted boldslanted type cap small... COMMAND  
expansion = yes no command

`\setupspacing` [...]

\* broad packed

`\setupstrut` [...]

\* yes no cap TEXT

`\setupsubpagenumber` [<sup>\*</sup>...<sub>OPTIONAL</sub>...]

\* way = bytext bycd:section  
state = start stop none

`\setupsymbolset` [...]

\* IDENTIFIER

`\setupsynchronization` [<sup>\*</sup>...<sub>OPTIONAL</sub>...]

\* state = start stop

`\setupsynchronizationbar` [<sup>\*</sup>...<sub>OPTIONAL</sub>...]

\* alternative = page local  
width = DIMENSION height fit  
height = DIMENSION  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
*inherits from* \setupframed

`\setupsynonyms` [<sup>1</sup>...] [<sup>2</sup>...<sub>OPTIONAL</sub>...]

1 IDENTIFIER  
2 textstyle = normal bold slanted boldslanted type cap small... COMMAND  
synonymstyle = normal bold slanted boldslanted type cap small... COMMAND  
location = left right top serried inmargin inleft inright  
width = DIMENSION  
state = start stop  
criterium = all used  
conversion = yes no  
expansion = yes no command  
command = \...#1#2#3

`\setupsystem [..,*.,..]`

\* resolution = NUMBER  
file = TEXT  
directory = TEXT  
random = normal small medium big NUMBER

`\setuptab [..,*.,..]`

\* sample = TEXT  
width = DIMENSION  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
location = left right

`\setuptables [..,*.,..]`

\* distance = small medium big  
bodyfont = 5pt ... 12pt small big  
HL = NUMBER small medium big none  
VL = NUMBER small medium big none  
depth = NUMBER strut  
height = NUMBER strut  
rulethickness = DIMENSION  
rulecolor = IDENTIFIER  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l  
12r  
commands = COMMAND  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l  
12r  
background = screen color none  
backgroundscreen = NUMBER  
backgroundcolor = IDENTIFIER  
bodyfont = 5pt ... 12pt small big

`\setuptabulate [.1.] [..,2.,..]`

OPTIONAL  
1 IDENTIFIER  
2 unit = DIMENSION  
indenting = never none not no yes always first next small medium big normal odd even DIMENSION  
before = COMMAND  
after = COMMAND  
inner = COMMAND  
EQ = TEXT  
rulecolor = IDENTIFIER  
align = inner outer left right flushleft flushright middle center normal no yes broad last r2l 12r  
rulethickness = DIMENSION  
distance = blank grid depth DIMENSION small medium big none  
bodyfont = 5pt ... 12pt small big  
rule = normal line  
split = yes no

`\setuptext [.1.] [..,2.,..]`

OPTIONAL  
1 inherits from \setupheader  
2 inherits from \setupheader

`\setuptextrules [..,*.,..]`

\* location = left inmargin  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
width = DIMENSION  
distance = DIMENSION  
bodyfont = 5pt ... 12pt small big  
color = IDENTIFIER  
style = normal bold slanted boldslanted type cap small... COMMAND  
rulecolor = IDENTIFIER

`\setuptexttexts [.1.] [.2.] [.3.]`

OPTIONAL  
1 text margin edge  
2 TEXT SECTION date MARK pagenumber  
3 TEXT SECTION date MARK pagenumber

## `\setupthinrules [.*.]`

\* interlinespace = small medium big  
n = NUMBER  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
color = IDENTIFIER  
backgroundcolor = IDENTIFIER  
height = DIMENSION max  
depth = DIMENSION max  
alternative = a b c d  
rulethickness = DIMENSION  
color = IDENTIFIER  
background = color  
backgroundcolor = IDENTIFIER

## `\setuptolerance [...,*,...]`

\* horizontal vertical stretch space verystrict strict tolerant verytolerant

## `\setuptop [.1.] [...,.2.,...]`

OPTIONAL  
1 inherits from \setupheader  
2 inherits from \setupheader

## `\setuptotexts [.1.] [.2.] [.3.]`

OPTIONAL  
1 text margin edge  
2 TEXT SECTION date MARK pagenumber  
3 TEXT SECTION date MARK pagenumber

## `\setuptype [...,*,...]`

\* space = on off  
option = slanted normal none  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
left = COMMAND  
right = COMMAND  
command = COMMAND

## `\setuptyping [.1.] [...,.2.,...]`

OPTIONAL  
1 file typing IDENTIFIER  
2 space = on off  
page = yes no  
option = slanted normal commands color none  
text = yes no  
icommand = COMMAND  
vcommand = COMMAND  
ccommand = COMMAND  
before = COMMAND  
after = COMMAND  
margin = DIMENSION standard yes no  
evenmargin = DIMENSION  
oddmargin = DIMENSION  
blank = DIMENSION small medium big standard halflines line  
escape = TEXT  
space = on off  
tab = NUMBER yes no  
page = yes no  
indentnext = yes no  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
palet = IDENTIFIER  
range = TEXT  
lines = yes no hyphenated  
empty = yes all no  
numbering = line file no  
bodyfont = 5pt ... 12pt small big  
strip = no auto NUMBER

`\setupunderbar [..,*.,..]`

\* `alternative` = a b c  
\* `rulethickness` = DIMENSION  
\* `bottomoffset` = DIMENSION  
\* `topoffset` = DIMENSION  
\* `rulecolor` = IDENTIFIER

`\setupurl [..,*.,..]`

\* `style` = normal bold slanted boldslanted type cap small... COMMAND  
\* `urlalternative` = none both before after  
\* `urlspace` = yes no

`\setupversions [..,*.,..]`

\* `number` = NUMBER  
\* `style` = normal bold slanted boldslanted type cap small... COMMAND

`\setupwhitespace [.*.]`

OPTIONAL  
\* `none` small medium big line fixed fix DIMENSION

`\showbodyfont [..,*.,..]`

OPTIONAL  
\* `inherits from` \setupbodyfont

`\showbodyfontenvironment [..,*.,..]`

OPTIONAL  
\* `inherits from` \setupbodyfont

`\showcolor [.*.]`

\* IDENTIFIER

`\showcolorgroup [.*.] [...2;...]`

1 IDENTIFIER  
2 horizontal vertical name value NUMBER

`\showexternalfigures [..,*.,..]`

OPTIONAL  
\* `alternative` = a b c

`\showfields [..,*.,..]`

OPTIONAL  
\* IDENTIFIER

`\showframe [.*.]`

OPTIONAL  
\* TEXT margin edge

`\showgrid [...1;...] {.*.}`

OPTIONAL  
1 reset top bottom none all lines frame nonumber right left outer  
2 CONTENT

`\showlayout`

`\showmakeup`

`\showpalet [.*.] [...2;...]`

1 IDENTIFIER  
2 horizontal vertical name value

`\showprint [...1,...] [...2,...] [...3,...]`

1 *inherits from* \setuppapersize  
2 *inherits from* \setuppapersize  
3 *inherits from* \setuplayout

`\showsetups`

`\showstruts`

`\showsymbolset [...]`

\* IDENTIFIER

`\someline [...]`

\* REFERENCE

`\somewhere {.1.} {.2.} [.3.]`

1 CONTENT  
2 CONTENT  
3 REFERENCE

`\SORT [.1.] {.2.}`

1 TEXT  
2 CONTENT

`\space`

`\splitfloat [...,1,...] {.2.} {.3.}`

OPTIONAL  
1 *inherits from* \setupfloatsplitting  
2 CONTENT  
3 CONTENT

`\startalignment [...*,...] ... \stopalignment`

OPTIONAL  
\* *inherits from* \setupalign

`\startbackground {.*} ... \stopbackground`

\* CONTENT

`\startbuffer [...] ... \stopbuffer`

OPTIONAL  
\* IDENTIFIER

`\startBUFFER [...] ... \stopBUFFER`

OPTIONAL  
\* IDENTIFIER

`\startcolor [...] ... \stopcolor`

\* IDENTIFIER

`\startcolumns [...,*,...] ... \stopcolumns`

OPTIONAL  
\* *inherits from* \setupcolumns

`\startcombination [...] ... \stopcombination`

\* N\*M

`\startcomment` [<sup>1</sup>.] [OPTIONAL...,<sup>2</sup>..,...] ... `\stopcomment`

- 1 IDENTIFIER
- 2 *inherits from* `\setupcomment`

`\startcomponent` ... .. `\stopcomponent`

- \* FILE NAME

`\startDESCRIPTION` {...} ... `\stopDESCRIPTION`

- \* CONTENT

`\startdocument` [...].] ... `\stopdocument`

- \* IDENTIFIER

`\startENUMERATION` ... `\stopENUMERATION`

`\startenvironment` ... .. `\stopenvironment`

- \* FILE NAME

`\startfact` .<sup>1</sup>. .<sup>2</sup>. .<sup>3</sup>. ... `\stopfact`

- 1 NOTHING
- 2 NOTHING
- 3 NOTHING

`\startfigure` [<sup>1</sup>.] [<sup>2</sup>.] [OPTIONAL...,<sup>3</sup>..,...] ... `\stopfigure`

- 1 IDENTIFIER
- 2 FILE
- 3 `factor = NUMBER`
- `frame = on off`

`\startFLOATtext` [<sup>1</sup>.] [<sup>2</sup>.] [OPTIONAL{.<sup>3</sup>.} [OPTIONAL{.<sup>4</sup>.}] ... `\stopFLOATtext`

- 1 left right high middle low offset tall
- 2 REFERENCE
- 3 CONTENT
- 4 CONTENT

`\startFORMULA` ... `\stopFORMULA`

`\startFRAMEDTEXT` [<sup>1</sup>.] [OPTIONAL...,<sup>2</sup>..,...] ... `\stopFRAMEDTEXT`

- 1 left right middle none
- 2 *inherits from* `\setupframedtexts`

`\starthiding` ... `\stophiding`

`\startinteractionmenu` [...].] ... `\stopinteractionmenu`

- \* IDENTIFIER

`\startITEMGROUP` [<sup>1</sup>.] [OPTIONAL...,<sup>2</sup>..,...] [OPTIONAL...,<sup>3</sup>..,...] ... `\stopITEMGROUP`

- 1 IDENTIFIER
- 2 a A KA n N m r R KR NUMBER continue standard broad serried packed stopper joinedup atmargin inmargin intro columns text paragraph repeat
- 3 *inherits from* `\setupitemgroup`

`\startlegend [...]1 .2 .3 .4 ... \stoplegend`

OPTIONAL

- 1 two
- 2 NOTHING
- 3 NOTHING
- 4 NOTHING

`\startline [...]* ... \stopline`

- \* REFERENCE

`\startlinecorrection ... \stoplinecorrection`

`\startlinenumbering [...]* ... \stoplinenumbering`

- \* continue

`\startlines ... \stoplines`

`\startlocal ... \stoplocal`

`\startlocalenvironment ... \stoplocalenvironment`

`\startlocalfootnotes ... \stoplocalfootnotes`

`\startmakeup [...]1 [...,2...]OPTIONAL ... \stopmakeup`

OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupmakeup

`\startmarginblock ... \stopmarginblock`

`\startmarginrule [...]* ... \stopmarginrule`

- \* NUMBER

`\startNAMEmakeup ... \stopNAMEmakeup`

`\startnarrower [...]*...]OPTIONAL ... \stopnarrower`

OPTIONAL

- \* left middle right -left -middle -right -none

`\startopposite ... \stopopposite`

`\startoverlay {...}1 {...}2 ... \stopoverlay`

- 1 CONTENT
- 2 CONTENT

`\startoverview [...]*...]OPTIONAL ... \stopoverview`

- \* IDENTIFIER

`\startpacked [...]* ... \stoppacked`

OPTIONAL

- \* blank

`\startPARAGRAPH ... \stopPARAGRAPH`

`\startpositioning ... \stoppositioning`

`\startpostponing ... \stoppostponing`

`\startproduct *. ... \stopproduct`

\* FILE NAME

`\startprofile [...*...] ... \stopprofile`

\* IDENTIFIER

`\startproject *. ... \stopproject`

\* FILE NAME

`\startquotation [...*...] ... \stopquotation`

\* left middle right

`\startREGISTER [.1.] {..2.+..}`

OPTIONAL

1 TEXT  
2 INDEX

`\startsymbolset [...*] ... \stopsymbolset`

\* IDENTIFIER

`\startsynchynchronization ... \stopsynchynchronization`

`\starttable [...*] ... \stoptable`

\* TEXT IDENTIFIER

`\starttables [...*] ... \stoptables`

\* TEXT IDENTIFIER

`\startTABULATE [.1.] [...,2.,...] ... \stopTABULATE`

OPTIONAL

OPTIONAL

1 TEXT  
2 *inherits from* \setupeexternalfigures

`\starttextrule [.1.] {..2.} ... \stoptextrule`

OPTIONAL

OPTIONAL

1 top bottom  
2 CONTENT

`\startTYPING ... \stopTYPING`

`\startunpacked ... \stopunpacked`

`\startversion [...*...] ... \stopversion`

\* NUMBER

`\stretched {...}`

\* WORD

`\sub [...*...]`

OPTIONAL

\* REFERENCE

`\subject [...1;...] {..2}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\subsection [...1;...] {..2}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\subsubject [...1;...] {..2}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\subsubsection [...1;...] {..2}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\subsubsubject [...1;...] {..2}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\switchtobodyfont [...*,...]`

\* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt  
small big

`\sym {..}`

\* CONTENT

`\symbol [..1] [..2]`

OPTIONAL  
1 IDENTIFIER  
2 IDENTIFIER

`\synchronizationbar [..1] [...,..2,...]`

1 IDENTIFIER  
2 alternative = page local  
*inherits from \setupsynchronizationbar*

`\synchronize`

`\SYNONYM [..1] {..2} {..3}`

OPTIONAL  
1 TEXT  
2 CONTENT  
3 CONTENT

`\tab {..1} ..2.`

1 CONTENT  
2 NOTHING

`\tex {..}`

\* CONTENT

`\textreference [..1] {..2}`

1 REFERENCE  
2 CONTENT

`\textrule [.1.] {.2.}`

OPTIONAL    OPTIONAL  
1 top bottom  
2 CONTENT

`\thinrule`

`\thinrules [.*.]`

OPTIONAL  
\* inherits from \setupthinrules

`\title [...1,...] {.2.}`

OPTIONAL  
1 REFERENCE  
2 CONTENT

`\tooltip [.1.] {.2.} {.3.}`

OPTIONAL  
1 left right middle  
2 CONTENT  
3 CONTENT

`\translate [...,*,...]`

\* IDENTIFIER = TEXT

`\typ {.*}`

\* CONTENT

`\type {...}`

\* CONTENT

`\typebuffer [.*]`

\* IDENTIFIER

`\typefile [.1.] {.2.}`

OPTIONAL  
1 IDENTIFIER  
2 CONTENT

`\underbar {...}`

\* CONTENT

`\underbars {...*...}`

\* WORD

`\useblocks [...1,...] [...2,...]`

OPTIONAL  
1 IDENTIFIER  
2 IDENTIFIER

`\usecommands {...}`

\* CONTENT

`\usedirectory [...*,...]`

\* IDENTIFIER reset

`\useencoding [...*...]`

\* IDENTIFIER

`\useexternaldocument [.1.] [.2.] [.3.]`

1 IDENTIFIER  
2 file  
3 TEXT

`\useexternalfigure [.1.] [.2.] [.3.] [...4...]`

1 IDENTIFIER  
2 FILE  
3 IDENTIFIER  
4 *inherits from \setupexternalfigures*

`\useexternalfile [.1.] [.2.] [.3.] [...4...]`

1 IDENTIFIER  
2 IDENTIFIER  
3 FILE  
4 bodyfont = 5pt ... 12pt small big

`\useexternalfiles [.1.] [...2...]`

1 IDENTIFIER  
2 bodyfont = 5pt ... 12pt small big  
file = FILE

`\useexternalsoundtrack [.1.] [.2.]`

1 IDENTIFIER  
2 FILE

`\usemodule [...*...]`

\* IDENTIFIER

`\userferences [...*...]`

\* FILE

`\usespecials [...*...]`

\* reset IDENTIFIER

`\usesymbols [...*...]`

\* IDENTIFIER

`\usetypescript [...1...] [...2...] [...3...]`

1 IDENTIFIER  
2 IDENTIFIER  
3 IDENTIFIER

`\usetypescriptfile [...*...]`

\* FILE

`\useURL [.1.] [.2.] [.3.] [.4.]`

1 IDENTIFIER  
2 TEXT  
3 file  
4 TEXT

\version [...]

\* final concept temporary

\v1 [...]

\* NUMBER

\WEEKDAY {...}

\* CONTENT

\WORD {...}

\* WORD

\WORDS {... ..}

\* WORD

\Word {...}

\* WORD

\Words {... ..}

\* WORD

\weekday {...}

\* CONTENT

\whitespace

\wordright {...}

\* CONTENT

\writebetweenlist [.<sup>1</sup>.] [...,2.,...] {.<sup>3</sup>.}

1 SECTION IDENTIFIER  
2 location = here none  
3 CONTENT

\writetolist [.<sup>1</sup>.] [...,2.,...] {.<sup>3</sup>.} {.<sup>4</sup>.}

1 SECTION IDENTIFIER  
2 location = here none  
3 CONTENT  
4 CONTENT

\writetoreferencelist [.<sup>1</sup>.] {.<sup>2</sup>.} {.<sup>3</sup>.}

1 IDENTIFIER  
2 CONTENT  
3 CONTENT

\writetoregister [.<sup>1</sup>.] [2.] {..<sup>3</sup>..+..}

1 SINGULAR NAME  
2 TEXT  
3 INDEX

OPTIONAL



**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**

